

Filtration system with sediment perfiltration, activated carbon and ultrafiltration membrane in 2,5" cartridge.

The system do not produce waste water and do not remove any minerals.

## TECHNICAL SPECIFICATION

PARAMETER	VALUE
Dimensions	420 x 320 x 100 mm
Connection to tap water system	3/8", 1/2", 3/4"
Connection outside the casing	1/4"
Maximum capacity	3,8 l/min
Operating pH	2 - 11
Operating pressure	2,2- 6 bar
Operating temperature	2 - 38 °C
Includes:	<ul style="list-style-type: none"><li>▪ In-line Sediment Cartridge [AC-IL-PP]</li><li>▪ In-line Granular Carbon Cartridge [AC-IL-GAC]</li><li>▪ In-line Sediment Cartridge [AC-IL-PP]</li><li>▪ Ultrafiltration Membrane [AC-BIL-HF-QC]</li><li>▪ Single Ceramic Faucet [AP-CF-1-1H]</li></ul>
Functions	<ul style="list-style-type: none"><li>▪ high reduction of unpleasant taste and odour,</li><li>▪ removes mechanical impurities,</li><li>▪ reduces high molecular-weight substances, colloidal materials, and organic and inorganic polymeric molecules above 0,1 micron. Low molecular-weight organics and ions such as sodium, calcium, magnesium, chloride, and sulfate are not removed.</li></ul>